

IN THE DESCRIPTION

Please amend the paragraph starting at page 15, line 5 to read as follows:

FIG. 4A is a brushless vibration motor according to an embodiment of the present invention;

FIG. 4B is an enlarged, fragmentary view of the central portion of FIG. 4A, and figures 4A and 4B will also be referred to collectively as "Fig. 4";

Please amend the paragraph starting at page 16, line 17 to read as follows:

FIG. 4A is a cross-sectional view of the brushless vibration motor, FIG. 4B is an enlarged, fragmentary view of the central portion of FIG. 4A, and figures 4A and 4B will also be referred to collectively as "Fig. 4." FIG. 5 is a partial perspective view of the brushless vibration motor shown in FIG. 4, and FIG. 6 is an exploded view of the brushless vibration motor shown in FIGS. 4 and 5.

After page 19, line 20 insert the following paragraph:

As best seen in Fig. 4B, there is an interior space defined between the bearing holder 220 and the bearing 222. In this embodiment, a hole h2 is formed in the wall of the bearing holder which surrounds the space, and the space communicates with the outside of the bearing holder through this hole. A hole h1 is also formed in the thrust washer 224 which communicates with the interior space of the bearing holder. This interior space is surrounded by the bearing 222, the thrust washer 224 and the shaft 105.